## **Timer Belt Actuator**

# SQ-50HA

### **Square Automation**

Contact: + 91 965733 2859 (Pune, MH)

+ 91 94225 48391

Email: square.automation@gmail.com

Web: www.square-automation.net





#### **Features**


- Driven by high quality Timer Belt, good repeatability and long lifetime
- New style shaft tip structure to prevent screw from loosing, very suitable for high speed reciprocating motion
- Adopt high precision linear slider guide, smooth motion and heavy load capacity, suitable for single axis heavy duty or multi-axis combination use
- Step motor and ball screw connected with high quality elastic coupler to get low noise Synchronous transmission
- Equipt with adjusting pulley, easy for debugging
- Zero position switch and limit switch at both ends for accurate positioning and protecting the product itself
- The base has threaded holes and thru holes, easy for installation
- Servo-motor can be installed for industrial application


Technical Parameters		
1	Model	SQ-50HA
2	Guide Width	50 x 52 mm
3	Load Capacity	15 Kg
4	Pitch	110 mm
5	Stroke Length	Up to 3 mtr
6	Moment load	10 Nm
7	Linear Accuracy	0.1 mm
8	Position Repeatability	0.05 mm
9	Material	Aluminum Profile
10	Carriage Size	130 x 108mm
11	Applicable Motor	NEMA 23 & 34 Standard Stepper Motor, 400W & 750W Servo Motor

### **Mechanical dimension**









## **Example**

